

**JAC**  
MOTORS



# JAC N90 6-TONNE CHASSIS CAB TRUCK

**SPECIFICATIONS**

JACMOTORS.CO.ZA



# N90 6-TONNE TRUCK

DESCRIPTION		N90 6-TONNE CHASSIS CAB
Mass Data (kg)	GVM	9 000
	GCM	12 500
	Tare Mass	3 000
	Tare Front	1 850
	Tare Rear	1 150
	GAWR Front	3 100
	GAWR Rear	6 600
	Approximate Body & Payload	5 920
Dimensional Data (mm)	Overall Length - OAL	6 970
	Wheelbase - WB	3 845
	Overall Width - OW	2 110
	Cab Width (Excluding Mirrors) - CW	1 995
	Overall Height - OH	2 300
	Bumper To Back Of Cab - BBC	1 680
	Cab to Axle - CA	3 245
	Cab To End Of Frame - CE	5 255
	Front Overhang - FOH	1 110
	Rear Overhang - ROH	2 010
	Ground Clearance (Rear Axle)	210
	Frame Width	850
	Rear Track - RT	1 650
	Engine	Make
Model		ISF 3.8
Configuration		Inline 4 Cylinder
Capacity (cc)		3 800
Emission Level		Euro III
Type		4 Stroke Diesel Turbocharged Intercooled
Injector Type		Common Rail Pump
Engine Oil Cooler		Yes
Valve Configuration		OHV
Power @ RPM (kW)		115 @ 2600
Torque @ RPM (Nm)	500 @ 1200 - 1900	
Transmission	Make	JAC
	Model	LC6T540B
	Type	Synchromesh (2 - 6 Only)
	Shift	Manual
	No. Of Forward Gears	6
	First Gear Ratio	6.091 : 1
	Reverse Gear Ratio	5.645 : 1
Safety	Reverse Alarm	Yes
	Seat Belt Warning	Yes
	Height Adjustable Seat Belt	Driver
	Height Adjustable Headlights	Yes
	LED Daytime Running Lights	Yes
	Antilock Braking System (ABS)	Yes
	Microdot Vehicle Identification	Yes

DESCRIPTION		N90 6-TONNE CHASSIS CAB
Clutch	Type	Diaphragm Spring
	Diameter (mm)	350
	Operation	Hydraulic Assistance
Suspension	Front & Rear	Multi-Leaf Spring With Shock Absorbers
Steering	Steering Column	Tilt And Telescoping
	Type	Recirculating Ball
	Operation	Power Assisted
Brakes	Type	Dual Circuit Air Brakes
	Anti-Lock Braking System (ABS)	Yes
	Air Dryer	Yes
	Front	Drum
	Rear	Drum
	LSP Valve On Rear Axle	Yes
	Parking Brake	Spring Brake On Rear Wheels
	Exhaust Brake	Yes
Fuel Tank	Material	Steel
	Capacity (Litres)	114
	Lockable Fuel Cap	Yes
Vehicle Performance	Maximum Gradeability (%)	30
	Maximum Allowable Speed (km/h) (SA SL)	80
Electrical Equipment	System	24V
	Battery System	2 X 80A-H
	Alternator	24V 70 Amp
	Starter	24V 3.6kW
Wheels & Tyres	Wheel Type	Single Piece Steel
	Wheel Attachment	6 Stud
	No. Of Wheels Including Spare	7
	Spare Wheel Carrier Location	Rear Of Frame
Tyre Size	215/75R17.5 16PLY	
Comfort Configuration	Air Conditioning	Yes
	Heater	Yes
	Power Windows	Yes
	Central Locking	Yes
	Number Of Seats	3
	12V Accessory Power Outlet	Yes
	Radio	AM/FM With AUX And USB
Cup Holders	Yes	
Lockable Toolbox At Rear Of Frame	Yes	



## JAC WARRANTY & SERVICE PLAN

- 2 Year / Unlimited km Warranty
- Service Plan Available On Request

### Service intervals:

- 10 000km / 3 Months
- 25 000km / 6 Months
- 40 000km / 12 Months

\* Thereafter every 15 000km / 6 Months



24-Hour Roadside Assistance



**BETTER DRIVE | BETTER LIFE**

\*Terms & Conditions apply. Offer available while stocks last. Prices may change without any prior notification. Images used are for illustrative purposes only. Actual products and specifications may vary from above information.

**JAC**  
MOTORS



# JAC N90 6-TONNE DROPSIDE TRUCK

**SPECIFICATIONS**

[JACMOTORS.CO.ZA](http://JACMOTORS.CO.ZA)



# N90 6-TONNE TRUCK

DESCRIPTION		N90 6-TONNE DROPSIDE
Mass Data (kg)	GVM	9 000
	GCM	12 500
	Tare Mass	3 800
	Tare Front	1 965
	Tare Rear	1 835
	GAWR Front	3 100
	GAWR Rear	6 600
	Approximate Body & Payload	5 200
Dimensional Data (mm)	Overall Length - OAL	7 030
	Wheelbase - WB	3 845
	Overall Width - OW	2 275
	Cab Width (Excluding Mirrors) - CW	1 995
	Overall Height - OH	2 300
	Bumper To Back Of Cab - BBC	1 680
	Cab to Axle - CA	3 245
	Cab To End Of Frame - CE	5 255
	Front Overhang - FOH	1 110
	Rear Overhang - ROH	2 078
	Ground Clearance (Rear Axle)	210
	Frame Width	850
	Rear Track - RT	1 650
	Dropside Body Inner Length	5 135
	Dropside Inner Width	2 110
Dropside Side Height	550	
Engine	Make	Cummins
	Model	ISF 3.8
	Configuration	Inline 4 Cylinder
	Capacity (cc)	3 800
	Emission Level	Euro III
	Type	4 Stroke Diesel Turbocharged Intercooled
	Injector Type	Common Rail Pump
	Engine Oil Cooler	Yes
	Valve Configuration	OHV
	Power @ RPM (kW)	115 @ 2600
Torque @ RPM (Nm)	500 @ 1200 - 1900	
Transmission	Make	JAC
	Model	LC6T540B
	Type	Synchromesh (2 - 6 Only)
	Shift	Manual
	No. Of Forward Gears	6
	First Gear Ratio	6.091 : 1
	Reverse Gear Ratio	5.645 : 1
Safety	Reverse Alarm	Yes
	Seat Belt Warning	Yes
	Height Adjustable Seat Belt	Driver
	Height Adjustable Headlights	Yes
	LED Daytime Running Lights	Yes
	Antilock Braking System (ABS)	Yes
Microdot Vehicle Identification	Yes	

DESCRIPTION		N90 6-TONNE DROPSIDE
Clutch	Type	Diaphragm Spring
	Diameter (mm)	350
	Operation	Hydraulic Assistance
Suspension	Front & Rear	Multi-Leaf Spring With Shock Absorbers
Steering	Steering Column	Tilt And Telescoping
	Type	Recirculating Ball
	Operation	Power Assisted
Brakes	Type	Dual Circuit Air Brakes
	Anti-Lock Braking System (ABS)	Yes
	Air Dryer	Yes
	Front	Drum
	Rear	Drum
	LSP Valve On Rear Axle	Yes
	Parking Brake	Spring Brake On Rear Wheels
	Exhaust Brake	Yes
Fuel Tank	Material	Steel
	Capacity (Litres)	114
	Lockable Fuel Cap	Yes
Vehicle Performance	Maximum Gradeability (%)	30
	Maximum Allowable Speed (km/h) (SA SL)	80
Electrical Equipment	System	24V
	Battery System	2 X 80A-H
	Alternator	24V 70 Amp
	Starter	24V 3.6kW
Wheels & Tyres	Wheel Type	Single Piece Steel
	Wheel Attachment	6 Stud
	No. Of Wheels Including Spare	7
	Spare Wheel Carrier Location	Rear Of Frame
	Tyre Size	215/75R17.5 16PLY
Comfort Configuration	Air Conditioning	Yes
	Heater	Yes
	Power Windows	Yes
	Central Locking	Yes
	Number Of Seats	3
	12V Accessory Power Outlet	Yes
	Radio	AM/FM With AUX And USB
	Cup Holders	Yes
Lockable Toolbox At Rear Of Frame	Yes	



## JAC WARRANTY & SERVICE PLAN

- 2 Year / Unlimited km Warranty
- Service Plan Available On Request

### Service intervals:

- 10 000km / 3 Months
- 25 000km / 6 Months
- 40 000km / 12 Months

\* Thereafter every 15 000km / 6 Months



24-Hour Roadside Assistance



**BETTER DRIVE | BETTER LIFE**

\*Terms & Conditions apply. Offer available while stocks last. Prices may change without any prior notification. Images used are for illustrative purposes only. Actual products and specifications may vary from above information.